



Industries, Inc.

Designer and Manufacturer of **AccessAbility**. Automatic Door Activation Solutions

6X6 SERIES (6" Square) Short Form Specifications

6 inch Square Automatic Door Activation switch by Wikk Industries, Inc.

Features: Smooth Rounded Corners, high quality images and text, tamper resistant by reason of no visible mounting screws.

Size: 6" x 6" (152 mm x 152 mm) square cover plate

Logo: Debossed or Engraved with infill colors as shown in literature, or custom Engraved and infilled with your choice of colors-Blue, Black, White, Red, Green and Chocolate Brown.

Material: Type 304 Stainless Steel in brushed finish US32D (630)

Optional Materials/Finishes: US32 (629), US3 (605), US4 (606), and US10B (613)

Switch Mechanism: UL® & CSA tested momentary SPDT snap action switch rated at 15 Amp 125/250 VAC

Mounting Plate: 4.5" x 4.5" Aluminum, 1/8" thick

Mounting:

Flush mount: single or double gang and 4x4 electrical boxes (requires 3/4" depth)

Surface mount: Wikk's products

Surf Sq. 4 & 6 Black (ABS material)

Surf 6/M Dark Bronze (710) or Clear (628) Anodized aluminum ring

4X4 BOX SLEEVE in Satin Stainless Steel US32D (630), Mirror US32 (629) and Satin Brass US4(606) and Mirror US3(605)

Switch projection from mounting surface: approximately 5/8" (15.8 mm)

WR (Weather Resistant) option: Rubber dome seal protects switch mechanism to effectively block dirt and moisture from damaging snap action switch.

Specified in:

MasterFormat® 1995: Section 08 710 Door Hardware

MasterFormat® 2004: Section 08 7120 Automatic Door Controls

From 4SPECs website: Section 08 7120 Door Controllers and Operators

CSI 3- Part Format Guide Specifications are available for download on the

Wikk's Website: <http://www.wikk.com>

Exclusive
Manufacturer of
the
INGRESS'R®



36" inches of
enlightened access
for
automatic doors