

RECESSED INSERT AREA FOR STANDARD WIKK 4-1/2" SQUARE AND 4-1/2" ROUND SWITCHES ALSO ACCOMMODATES KEY SWITCHES, CARD READERS AND PROXIMITY READERS WITH SIMILAR DIMENSIONS

SHOWN WITH WIKK 4X4-5 SWITCH (OPTIONAL)

MATERIAL: STAINLESS STEEL TYPE 304  
 FINISH: SATIN (630 US32D) OR MIRROR (629 US32)

OR


MATERIAL: MILL ALUMINUM TYPE 6063  
 FINISH: FOR PAINTING OR POWDER COATING

DIFFERENT BOLLARD HEIGHTS AND SWITCH LOCATIONS AVAILABLE UPON REQUEST

IN GROUND VERSION ALSO AVAILABLE

- 1/2" HEAVY DUTY MASONRY ANCHORS, MINIMUM ENGAGEMENT 1 1/4" DEEP
- NEC CLASS II CIRCUIT (BY OTHERS)
- 1/4" THICK ALUMINUM BOLLARD MOUNTING BRACKET
- 1/4-20 STAINLESS STEEL F.H.M.S.
- MASONRY MOUNTING SURFACE

Exact product dimensions and features may vary slightly from example shown above.

		Wikk Industries, Inc. 6169 Industrial Ct. Greendale, WI 53129-0167 Phone: 414-421-9490 Fax: 414-421-3158	
		SCALE N.T.S.	DRAWN BY/DATE JK/06JAN12
TITLE BPRSM-AINS			
DRAWING NUMBER J:BOLLARDS\BOLLARD LITERATURE\BPRSM-AINS			
WIKK PART NO. BPRSM-AINS			