



Ø1.5" HOLE THROUGH BOLLARD
MOUNTING BRACKET FOR CONDUIT

MOUNTING HOLES
(4 PLACES)

1/2" THICK MORTISED BOLLARD CAP,
R.F. TRANSPARENT (BLACK)

#4-40 SET SCREWS,
DO NOT OVER TIGHTEN

STRAP FOR OPTIONAL TRANSMITTER,
CONNECT WIRES TO SWITCH

SINGLE GANG MOUNT PREP FOR:
WIKK STANDARD 4 1/2" AND 6"
SWITCHES, AND A VARIETY OF
KEY SWITCHES, CARD READERS,
PROXIMITY READERS, ETC.
AT 7" AND 36"

1/8" [3mm]

1/2" HEAVY DUTY MASONRY ANCHORS,
MINIMUM ENGAGEMENT 1 1/4" DEEP

NEC CLASS II CIRCUIT (BY OTHERS)

1/4" THICK ALUMINUM
BOLLARD MOUNTING BRACKET

1/4-20 STAINLESS STEEL F.H.M.S.

MASONRY MOUNTING SURFACE

AVAILABLE FINISHES: ANODIZED ALUMINUM, CLEAR (628),
DARK BRONZE (710), BLACK (711), LIGHT BRONZE, AND
MILL FOR PAINTING OR POWDERCOATING

Exact product dimensions and features may vary slightly from example shown above.



Wikk Industries, Inc.
6169 Industrial Ct.
Greendale, WI 53129-0167
Phone: 414-421-9490
Fax: 414-421-3158

SCALE N.T.S.	DRAWN BY/DATE JK/03OCT12	CHECKED BY/DATE LK/03OCT12
TITLE 6" SQUARE BOLLARD W/HIGH/LOW PREPS SURFACE MOUNT DETAIL		
DRAWING NUMBER J\BOLLARDS\ BOLLARD LITERATURE\BPS SM-HIGH-LOW ALUMINUM		
WIKK PART NO.		BPS SM-H/L ALUM