

BOLLARD

MATERIAL: ALUMINUM TYPE 6063-T5
STAINLESS STEEL TYPE 304

AVAILABLE FINISHES: ALUMINUM;
ANODIZED CLEAR (628), DARK BRONZE, (710)
LIGHT BRONZE, BLACK (711) AND MILL FOR PAINTING
OR POWDERCOATING

STAINLESS STEEL;
US32D (630) SATIN, US32 (629) MIRROR

INGRESS'R

MATERIAL: ALUMINUM TYPE 6063-T5
STAINLESS STEEL TYPE 304
BRASS TYPE 464

AVAILABLE FINISHES: ALUMINUM;
ANODIZED CLEAR (628) AND DARK BRONZE (710)

STAINLESS STEEL;
US32D (630) SATIN, US32 (629) MIRROR

BRASS;
US4 (606) SATIN UNCOATED,
US3 (605) MIRROR UNCOATED


1/2" X 2 3/4" HEAVY DUTY MASONRY ANCHORS
MINIMUM ENGAGEMENT 1 1/4" DEEP

NEC CLASS II CIRCUIT (BY OTHERS)

1/4" THICK ALUMINUM
BOLLARD MOUNTING BRACKET

1/4-20 STAINLESS STEEL F.H.M.S.

MASONRY MOUNTING SURFACE

			Wikk Industries, Inc. 6169 Industrial Ct. Greendale, WI 53129-0167 Phone: 877-421-9490 Fax: 877-421-3158		
SCALE	DRAWN BY/DATE	CHECKED BY/DATE			
N.T.S.	JK/09JAN12	LK/09JAN12			
TITLE					
BOLLARD WITH INGRESS'R					
DRAWING NUMBER					
BOLLARDS\BOLLARD LITERATURE\BPS-SM INGR					
WIKK PART NO.					
BPS SM-INGR					

Exact product dimensions and features may vary slightly from example shown above.