



Ø1.5" HOLE THROUGH BOLLARD MOUNTING BRACKET FOR CONDUIT

MOUNTING HOLES (4 PLACES)

1/2" THICK MORTISED BOLLARD CAP, R.F. TRANSPARENT (BLACK)

#4-40 SET SCREWS, DO NOT OVER TIGHTEN

STRAP FOR OPTIONAL TRANSMITTER, CONNECT WIRES TO SWITCH

SINGLE GANG MOUNT PREP FOR: WIKK STANDARD 4 1/2" AND 6" SWITCHES, AND A VARIETY OF KEY SWITCHES, CARD READERS, PROXIMITY READERS, ETC.

1/8" [3mm]

1/2" HEAVY DUTY MASONRY ANCHORS, MINIMUM ENGAGEMENT 1 1/4" DEEP

NEC CLASS II CIRCUIT (BY OTHERS)

1/4" THICK ALUMINUM BOLLARD MOUNTING BRACKET

1/4-20 STAINLESS STEEL F.H.M.S.

MASONRY MOUNTING SURFACE

AVAILABLE FINISHES: ANODIZED ALUMINUM, CLEAR (628), DARK BRONZE (710), BLACK (711), LIGHT BRONZE, AND MILL FOR PAINTING OR POWDERCOATING



Wikk Industries, Inc.  
6169 Industrial Ct.  
Greendale, WI 53129-0167  
Phone: 414-421-9490  
Fax: 414-421-3158

SCALE N.T.S.	DRAWN BY/DATE JK/12DEC11	CHECKED BY/DATE LK/12DEC11
TITLE 6" SQUARE BOLLARD W/SWITCH SURFACE MOUNT DETAIL		
DRAWING NUMBER J\BOLLARDS\ BOLLARD LITERATURE\BPS SM-PREP 36		
WIKK PART NO. BPS SM-PREP 36		

Exact product dimensions and features may vary slightly from example shown above.