



Wikk Industries, Inc.

Designer and Manufacturer of **AccessAbility**. Automatic Door Activation Solutions

SFA SERIES (Single Gang Full-Active) Short Form Specifications

SFA (2-3/4" x 4-1/2") Automatic Door Opening Full-Active Switch by Wikk Industries, Inc.

Features: Smooth rounded corners, high quality images and text, tamper resistant by reason of no visible mounting screws.

Size: 2-3/4" x 4-1/2" (70 mm x 114 mm) rectangular cover plate

Logo: Debossed or Engraved with infill colors as shown in literature, or custom Engraved and infilled with your choice of colors-Blue, Black, White, Red, Green and Chocolate Brown.

Material: Type 304 Stainless Steel in brushed finish US32D (630)

Optional Materials/Finishes: US32 (629), US3 (605), US4 (606), and US10B (613)

Switch Mechanism: UL® & CSA tested momentary SPDT snap action switch rated at 15 Amp 125/250 VAC

Mounting Plate: 2-3/4" x 4-1/2" Aluminum, 1/8" thick

Mounting:

Flush mount: single gang electrical box

Surface mount: Wikk's SURF SFA (brown phenolic material)

Switch projection from mounting surface: approximately 7/16" (11 mm)

WR (Weather Resistant) option: Rubber boot/panel nut component attached to switch mechanism onto the mounting plate to effectively block dirt and moisture from damaging snap action switch.

Specified in:

MasterFormat® 1995: Section 08 710 Door Hardware

MasterFormat® 2004: Section 08 7120 Automatic Door Controls

From 4SPECs website: Section 08 7120 Door Controllers and Operators

CSI 3- Part Format Guide Specifications are available for download on the

Wikk's Website: <http://www.wikk.com>

Exclusive
Manufacturer of
the
INGRESS'R®



36" inches of
enlightened access
for
automatic doors

Phone Toll Free: 877.421.9490
Phone: 414.421.9490
www.wikk.com

Fax Toll Free: 877.421.3158
Fax: 414.421.3158
sales@wikk.com

P.O. Box 167
6169A Industrial Court
Greendale, WI 53129-0167